




JT020N120WCD/ABCD/20N120C

主要参数 MAIN CHARACTERISTICS		封装 Package
I _c	20 A	
V _{ces}	1200 V	
V _{cesat_typ} (@V _{ge} =15V)	1.8V	
用途		APPLICATIONS
<ul style="list-style-type: none">逆变器电磁炉UPS 电源		<ul style="list-style-type: none">General purpose invertersInduction heating(IH)UPS
产品特性		FEATURES
<ul style="list-style-type: none">低栅极电荷FS 技术通态压降, V_{CE(sat)}, typ = 1.8V @ IC = 20A and TC = 25°CRoHS 产品		<ul style="list-style-type: none">Low gate chargeFS Technologysaturation voltage: V_{CE(sat)}, typ = 1.8V @ IC = 20A and TC = 25°CRoHS product



TO-247

TO-3PB

订货信息 ORDER MESSAGE

订货型号 Order codes	印 记 Marking	封 装 Package	无 卤 素 Halogen Free	包 装 Packaging	器件重量 Device Weight
JT020N120WCD-W-O-N-B	JT020N120WCD	TO-247	有卤 No	条管 Tube	6.0g(typ)
JT020N120ABCD-AB-O-N-B	JT020N120ABCD	TO-3PB	有卤 No	条管 Tube	5.1g(typ)
20N120C-W-O-N-B	20N120	TO-247	有卤 No	条管 Tube	6.0 g(typ)



JT020N120WCD/ABCD/20N120C

绝对最大额定值 ABSOLUTE RATINGS ($T_c=25^\circ\text{C}$)

项 目 Parameter	符 号 Symbol	数 值 Value		单 位 Unit
		JT020N120WCD/ABCD/20N120C		
最高集电极一发射极直流电压 Collector-Emitter Voltage	V_{ces}	1200		V
连续集电极极电流 Collector Current-continuous	I_C	40		A
	$T=100^\circ\text{C}$	20		A
最大脉冲集电极极电流 (注 1) Collector Current - pulse (note 1)	I_{CM}	60		A
最高栅极发射极电压 Gate-Emitter Voltage	V_{GES}	± 20		V
安全工作区 Turn-off safe area	-	60		A
耗散功率 Power Dissipation	P_D $T_c=25^\circ\text{C}$	350		W
最高结温及存储温度 Operating and Storage Temperature Range	T_J, T_{STG}	-55~+150		$^\circ\text{C}$
引线最高焊接温度 Maximum Lead Temperature for Soldering Purposes	T_L	300		$^\circ\text{C}$

*漏极电流由最高结温限制

*Collector current limited by maximum junction temperature



电特性 ELECTRICAL CHARACTERISTICS

项目 Parameter	符号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单位 Units
关态特性 Off -Characteristics						
集电极-发射极击穿电压 Collector-Emitter Voltage	BV_{CES}	$I_C=500\mu A, V_{GE}=0V$	1200	-	-	V
击穿电压温度特性 Breakdown Voltage Temperature Coefficient	$\Delta BV_{CES}/\Delta T_J$	$I_C=1mA$, referenced to 25°C	-	0.6	-	V/°C
零栅压下集电极漏电流 Zero Gate Voltage Collector Current	I_{CES}	$V_{CE}=1200V, V_{GE}=0V,$ $T_C=25^{\circ}C$	-	-	0.2	mA
		$T_C=100^{\circ}C$			2	mA
		$T_C=150^{\circ}C$	-	-	2.5	mA
正向栅极体漏电流 Gate-body leakage current, forward	I_{GESF}	$V_{CE}=0V, V_{GE}=20V$	-	-	100	nA
反向栅极体漏电流 Gate-body leakage current, reverse	I_{GESSR}	$V_{CE}=0V, V_{GE}=-20V$	-	-	-100	nA
通态特性 On-Characteristics						
阈值电压 Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$V_{CE}=V_{GE}, I_C=600\mu A$	4.5	-	6.5	V
饱和压降 Collector-Emitter saturation Voltage	V_{CESAT}	$V_{GE}=15V I_C=20A$ $T_c=25^{\circ}C$	-	1.8	2.45	
		$T_c=125^{\circ}C$	-	2.0	-	V
		$T_c=150^{\circ}C$	-	2.1	-	
短路电流 (注 2) Short Collector current (Note 2)	$I_{C(SC)}$	$V_{GE}=15V V_{CE}=600V t_{sc} < 10\mu s T_c=25^{\circ}C$		160		A
动态特性 Dynamic Characteristics						
输入电容 Input capacitance	C_{ies}	$V_{CE}=25V,$ $V_{GE}=0V,$ $f=1.0MHz$	-	1600	2400	pF
输出电容 Output capacitance	C_{oes}		-	120	190	pF
反向传输电容 Reverse transfer capacitance	C_{res}		-	84	130	pF



电特性 ELECTRICAL CHARACTERISTICS

开关特性 Switching Characteristics						
开启延迟时间 Turn-On delay time	$t_{\text{d(on)}}$	$V_{\text{CE}}=600V, I_{\text{C}}=20A, R_{\text{G}}=10\Omega$ $T_{\text{C}}=25^{\circ}\text{C}$ Inductive Load	-	90	-	ns
上升时间 Turn-On rise time	t_{r}		-	75	-	ns
关断延迟时间 Turn-Off delay time	$t_{\text{d(off)}}$		-	210	-	ns
下降时间 Turn-Off Fall time	t_{f}		-	100	-	ns
开启损耗 Turn-on energy	E_{on}		-	2.8	-	mJ
关断损耗 Turn-off energy	E_{off}		-	1.1	-	mJ
总的开关损耗 Total switching energy	E_{total}		-	3.9	-	mJ
栅极电荷总量 Total Gate Charge	Q_{g}		$V_{\text{CE}} = 600V, I_{\text{C}} = 20A$ $V_{\text{GE}} = 15V$ (note 3, 4)	-	115	nC

反并联二极管特性及最大额定值 Anti-Parallel Diode Characteristics and Maximum Ratings

正向压降 Diode Forward Voltage	V_{F}	$V_{\text{GE}}=0V, I_{\text{F}}=20A$	-	1.7	2.9	V
反向恢复时间 Diode Reverse recovery time	t_{rr}	$V_{\text{GE}}=0V, VR=800V I_{\text{F}}=20A$ $dI_{\text{F}}/dt=200A/\mu\text{s}$ (note 4)	-	230	-	ns
反向恢复电荷 Reverse recovery charge	Q_{rr}		-	1.2	-	μC

热特性 THERMAL CHARACTERISTIC







项 目 Parameter	符 号 Symbol	最 大 Max	单 位 Unit
结到管壳的热阻 Thermal Resistance, Junction to Case	$R_{\text{th(j-c)}}$	0.4	$^{\circ}\text{C}/\text{W}$
结到环境的热阻 Thermal Resistance, Junction to Ambient	$R_{\text{th(j-A)}}$	40	$^{\circ}\text{C}/\text{W}$

注释:


- 1: 脉冲宽度由最高结温限制
- 2: 两次短路之间的间隔大于 1 秒时, 允许短路测试的次数最大为 1000 次
- 3: 脉冲测试: 脉冲宽度 $\leq 300\mu\text{s}$, 占空比 $\leq 2\%$
- 4: 基本与工作温度无关

Notes:


- 1: Pulse width limited by maximum junction temperature
- 2: Allowed number of short circuits: <1000; time between short circuits: >1s.
- 3: Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$
- 4: Essentially independent of operating temperature

特征曲线 ELECTRICAL CHARACTERISTICS (curves)
Typical Output Characteristics($T_j=25^\circ\text{C}$)

Typical Output Characteristics($T_j=150^\circ\text{C}$)

Typical Saturation Voltage Characteristics

Saturation Voltage vs. Case Temperature at Variant Current Level

Capacitance Characteristics

Turn-On Characteristics vs. Gate Resistance



Turn-Off Characteristics vs. Gate Resistance




Switching Loss vs. Gate Resistance




Turn-On Characteristics vs. Collector Current




Turn-Off Characteristics vs. Collector Current










Switching Loss vs. Collector Current



Gate Charge Characteristics




SOA Characteristics

Turn-Off SOA

Transient Thermal Impedance

Forward Characteristics

Reverse Recovery Current


Stored Charge**Reverse Recovery Time**

外形尺寸 PACKAGE MECHANICAL DATA

TO-247


单位 Unit: mm



符号 symbol	MIN	MAX
A	4.90	5.10
B	2.95	3.35
B1	1.95	2.35
b	1.15	1.35
c	0.50	0.70
D	20.90	21.10
E	15.70	15.90
e	5.34	5.54
F	1.90	2.10
L	19.40	20.40
L2	4.03	4.23
Q	6.00	6.40
Q1	2.30	2.50
P	3.50	3.70

TO-3PB

单位 Unit: mm



符号 symbol	MIN	MAX
A	4.60	5.00
B	2.90	3.20
B1	1.90	2.20
b	0.90	1.10
c	0.50	0.70
D	19.40	20.40
E	15.40	15.80
e	5.45(TYP)	
F	1.40	1.60
L	19.50	20.50
L2	3.30	3.70
Q	4.90	5.10
Q1	1.30	1.50
P	3.10	3.50